

INTOXILYZER® 8000 INSTALLATION AND REPAIR CHECKOUT

NORTH DAKOTA OFFICE OF ATTORNEY GENERAL CRIME LABORATORY DIVISION-TOXICOLOGY SECTION/BREATH ALCOHOL PROGRAM SFN 59281 (06/2018)

Serial Number Instrument Location Reason for Install/Repair Instrument Location Mocton / Mandan LC	C/MAND			
Reason for Install/Repair				
Install After Receiving From Crime Laboratory Install After Location Change				
Other (Specify)				
Check When Done:				
1. Surge Protector Installed/Property Grounded.				
2. Telephone Line Connected to Intoxilyzer® 8000.				
3. Breath Tube Heated.				
4. Enter Preliminary Data (i.e. Date, Time, DST (Y), and Location; Level 2, Function E).				
5. Scan/Enter Gas Cylinder Information (Level 1, Function S).				
6. Run Tests:				
☑ A. Print Test (Level1, Function P).				
B. ACA Test (Level 1, Function C).				
C. Radio Frequency Interference (RFI) Test (CMS Mode or Level 1, Function B or C; Key Radio Du	uring Test).			
7. Repair and/or Maintenance Performed (if any):				
8. Complete the Top Portion of the Intoxilyzer® Record (SFN50496, Form 120-G) and Place it by the In	ntoxilyzer® for Use.			
9. File Previous Intoxilyzer® Record (SFN504096, Form 120-G) at the Intoxilyzer® Location at the Age	ency.			
10. Send the Following to the Crime Laboratory: Completed Intoxilyzer® 8000 Installation and Repair C 104-G), Print Test, ACA Test, and RFI Test.	heckout (SFN59281, Form			
Field Inspector Signature	Date			
	10/29/2020			
Crime Laboratory Use Only	/ /			
This installation has been reviewed and the instrument is approved to be used for the analysis of breath to deter the date the Field Inspector performed the installation. This record on file at the Office of Attorney General, Crim County of Burleigh, North Dakota, is certified to be a true and correct copy of the documents received.				
Reviewed/Certified By	Certified Date			

FORM 104-G

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer Alcohol Analyzer
North Dakota Model 8000 SN 80-007096
Location = MAND 8164.16.00 09/18
10/29/2020 15:15

********* Printer Test *********

abcdefghijklmnopqrstuvwxyz1234567890-=|
ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&*() +?

abcdefghijklmnopqrstuvwxyz1234567890-=| ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&*()_+?

Current Instrument Setup Enabled Data Entry Mode: **DABACABA** Start Test Sequence: Display Prelim Rslt? Yes Display Third Digit? Yes Inhib Printer(Y/N)? No No Display Volume? Disable On Memfull? Yes # of Print Copies? 1 Select Std (D/W/I)? Dry Standard Value? 0.080 Standard Lot #? 05620080A1 Standard Cyl #? 39 Standard Expiration? 04/05/2022 Oper No? 020611

Flow Cal. Date: 10/02/2018 Slope 695 Intercept -692605

IR Calibration Date:

3um 9um

Oth Coef(*100): -33544 -18475
1st Coef(*100): 261464 138054
2nd Coef(*100): 3020 1612
H2O adj(mg/l*10k): 573 386

10/02/2018

****** Printer Test End ********

Operator Signature TOM SHARP

Remarks:

Form 106-I8000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer
North Dakota Model 8000
Location = MAND
10/29/2020

SN 80-007096 8164.16.00 09/18 15:18

DRY CAL CHECK

Test			AC	Time
01	Room	Air	0.000	15:19
02	Std.	Gas	0.081	15:19
03	Room	Air	0.000	15:19
04	Std.	Gas	0.081	15:20
05	Room	Air	0.000	15:20
06	std.	Gas	0.081	15:21
07	Room	Air	0.000	15:21

Lot No = 05620080A1

Cyl No = 39

Exp Date = 04/05/2022

County = 30

Oper No. = 020611

Operator Signature
TOM SHARP

Remarks:

Form 106-I8000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer
North Dakota Model 8000
Location = MAND
10/29/2020

SN 80-007096 8164.16.00 09/18 15:23

DRY CAL CHECK

Test	AC	Time
01 Room Air	RFI*	15:23
02 Room Air	0.000	15:24

*Invalid Test Inhibited - RFI

Lot No = 05620080A1

Cyl No = 39

Exp Date = 04/05/2022

County = 30

Oper No. = 020611

Operator Signature
TOM SHARP

Remarks:

Form 106-I8000