

INTOXILYZER® 8000 INSTALLATION AND REPAIR CHECKOUT

NORTH DAKOTA OFFICE OF ATTORNEY GENERAL CRIME LABORATORY DIVISION-TOXICOLOGY SECTION/BREATH ALCOHOL PROGRAM SFN 59281 (06/2018)

Install After Receiving From Crime Laboratory Install After Location Change Other (Specify) Check When Done: 1. Surge Protector Installed/Property Grounded. 2. Telephone Line Connected to Intoxilyzer® 8000. 3. Breath Tube Heated. 4. Enter Preliminary Data (i.e. Date, Time, DST (Y), and Location; Level 2, Function E). 5. Scan/Enter Gas Cylinder Information (Level 1, Function S). 6. Run Tests: A. Print Test (Level1, Function P). 8. ACA Test (Level 1, Function C). C. Radio Frequency Interference (RFI) Test (CMS Mode or Level 1, Function B or C; Key Radio During Test). 7. Repair and/or Maintenance Performed (if any): 8. Complete the Top Portion of the Intoxilyzer® Record (SFN50496, Form 120-G) and Place it by the Intoxilyzer® for Use. 9. File Previous Intoxilyzer® Record (SFN504096, Form 120-G) at the Intoxilyzer® Location at the Agency. 10. Send the Following to the Crime Laboratory: Completed Intoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form 104-G), Print Test, ACA Test, and RFI Test.					
Install After Receiving From Crime Laboratory Install After Location Change Other (Specify) Check When Done: 1. Surge Protector Installed/Property Grounded. 2. Telephone Line Connected to Intoxilyzer® 8000. 3. Breath Tube Heated. 4. Enter Preliminary Data (i.e. Date, Time, DST (Y), and Location; Level 2, Function E). 5. Scan/Enter Gas Cylinder Information (Level 1, Function S). 6. Run Tests: A. Print Test (Level1, Function P). 8. ACA Test (Level 1, Function C). C. Radio Frequency Interference (RFI) Test (CMS Mode or Level 1, Function B or C; Key Radio During Test). 7. Repair and/or Maintenance Performed (if any): 8. Complete the Top Portion of the Intoxilyzer® Record (SFN50496, Form 120-G) and Place it by the Intoxilyzer® for Use. 9. File Previous Intoxilyzer® Record (SFN504096, Form 120-G) at the Intoxilyzer® Location at the Agency. 10. Send the Following to the Crime Laboratory: Completed Intoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form 104-G), Print Test, ACA Test, and RFI Test.	Serial Number 80-007098	Instrument Location	PD		
Check When Done: 1. Surge Protector Installed/Property Grounded. 2. Telephone Line Connected to Intoxilyzer® 8000. 3. Breath Tube Heated. 4. Enter Preliminary Data (i.e. Date, Time, DST (Y), and Location; Level 2, Function E). 5. Scan/Enter Gas Cylinder Information (Level 1, Function S). 6. Run Tests: A. Print Test (Level1, Function P). B. ACA Test (Level 1, Function C). C. Radio Frequency Interference (RFI) Test (CMS Mode or Level 1, Function B or C; Key Radio During Test). 7. Repair and/or Maintenance Performed (if any): 8. Complete the Top Portion of the Intoxilyzer® Record (SFN50496, Form 120-G) and Place it by the Intoxilyzer® for Use. 9. File Previous Intoxilyzer® Record (SFN50496, Form 120-G) at the Intoxilyzer® Location at the Agency. 10. Send the Following to the Crime Laboratory: Completed Intoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form 104-G), Print Test, ACA Test, and RFI Test.	Reason for Install/Repair				
Check When Done: 1. Surge Protector Installed/Property Grounded. 2. Telephone Line Connected to Intoxilyzer® 8000. 3. Breath Tube Heated. 4. Enter Preliminary Data (i.e. Date, Time, DST (Y), and Location; Level 2, Function E). 5. Scan/Enter Gas Cylinder Information (Level 1, Function S). 6. Run Tests: A. Print Test (Level1, Function P). 8. ACA Test (Level 1, Function C). 7. Repair and/or Maintenance Performed (if any): 8. Complete the Top Portion of the Intoxilyzer® Record (SFN50496, Form 120-G) and Place it by the Intoxilyzer® for Use. 9. File Previous Intoxilyzer® Record (SFN50496, Form 120-G) at the Intoxilyzer® Location at the Agency. 10. Send the Following to the Crime Laboratory: Completed Intoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form 104-G), Print Test, ACA Test, and RFI Test.	™ Install After Receiving From Crime Laboratory □ Install After Location Change				
Check When Done: 1. Surge Protector Installed/Property Grounded. 2. Telephone Line Connected to Intoxilyzer® 8000. 3. Breath Tube Heated. 4. Enter Preliminary Data (i.e. Date, Time, DST (Y), and Location; Level 2, Function E). 5. Scan/Enter Gas Cylinder Information (Level 1, Function S). 6. Run Tests: A. Print Test (Level1, Function P). 8. ACA Test (Level 1, Function C). C. Radio Frequency Interference (RFI) Test (CMS Mode or Level 1, Function B or C; Key Radio During Test). 7. Repair and/or Maintenance Performed (if any): 8. Complete the Top Portion of the Intoxilyzer® Record (SFN50496, Form 120-G) and Place it by the Intoxilyzer® for Use. 9. File Previous Intoxilyzer® Record (SFN504096, Form 120-G) at the Intoxilyzer® Location at the Agency. 10. Send the Following to the Crime Laboratory: Completed Intoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form 104-G), Print Test, ACA Test, and RFI Test.					
 Surge Protector Installed/Property Grounded. Telephone Line Connected to Intoxilyzer® 8000. Breath Tube Heated. Enter Preliminary Data (i.e. Date, Time, DST (Y), and Location; Level 2, Function E). Scan/Enter Gas Cylinder Information (Level 1, Function S). Run Tests: A. Print Test (Level1, Function P). B. ACA Test (Level 1, Function C). C. Radio Frequency Interference (RFI) Test (CMS Mode or Level 1, Function B or C; Key Radio During Test). T. Repair and/or Maintenance Performed (if any): Scomplete the Top Portion of the Intoxilyzer® Record (SFN50496, Form 120-G) and Place it by the Intoxilyzer® for Use. File Previous Intoxilyzer® Record (SFN504096, Form 120-G) at the Intoxilyzer® Location at the Agency. Send the Following to the Crime Laboratory: Completed Intoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form 104-G), Print Test, ACA Test, and RFI Test. 					
 Z 2. Telephone Line Connected to Intoxilyzer® 8000. ☑ 3. Breath Tube Heated. ☑ 4. Enter Preliminary Data (i.e. Date, Time, DST (Y), and Location; Level 2, Function E). ☑ 5. Scan/Enter Gas Cylinder Information (Level 1, Function S). ☑ 6. Run Tests: ☑ A. Print Test (Level1, Function P). ☑ B. ACA Test (Level 1, Function C). ☑ C. Radio Frequency Interference (RFI) Test (CMS Mode or Level 1, Function B or C; Key Radio During Test). ☑ 7. Repair and/or Maintenance Performed (if any): ☑ 8. Complete the Top Portion of the Intoxilyzer® Record (SFN50496, Form 120-G) and Place it by the Intoxilyzer® for Use. ☑ 9. File Previous Intoxilyzer® Record (SFN504096, Form 120-G) at the Intoxilyzer® Location at the Agency. 10. Send the Following to the Crime Laboratory: Completed Intoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form 104-G), Print Test, ACA Test, and RFI Test. 	Check When Done:				
3. Breath Tube Heated. 4. Enter Preliminary Data (i.e. Date, Time, DST (Y), and Location; Level 2, Function E). 5. Scan/Enter Gas Cylinder Information (Level 1, Function S). 6. Run Tests: A. Print Test (Level 1, Function P). 7. Repair and/or Maintenance Performed (if any): 8. Complete the Top Portion of the Intoxilyzer® Record (SFN50496, Form 120-G) and Place it by the Intoxilyzer® for Use. 9. File Previous Intoxilyzer® Record (SFN504096, Form 120-G) at the Intoxilyzer® Location at the Agency. 10. Send the Following to the Crime Laboratory: Completed Intoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form 104-G), Print Test, ACA Test, and RFI Test.	1. Surge Protector Installed/Property Grounded.				
4. Enter Preliminary Data (i.e. Date, Time, DST (Y), and Location; Level 2, Function E). 5. Scan/Enter Gas Cylinder Information (Level 1, Function S). 6. Run Tests: A. Print Test (Level 1, Function P). B. ACA Test (Level 1, Function C). C. Radio Frequency Interference (RFI) Test (CMS Mode or Level 1, Function B or C; Key Radio During Test). 7. Repair and/or Maintenance Performed (if any): 8. Complete the Top Portion of the Intoxilyzer® Record (SFN50496, Form 120-G) and Place it by the Intoxilyzer® for Use. 9. File Previous Intoxilyzer® Record (SFN504096, Form 120-G) at the Intoxilyzer® Location at the Agency. 10. Send the Following to the Crime Laboratory: Completed Intoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form 104-G), Print Test, ACA Test, and RFI Test.	2. Telephone Line Connected to Intoxilyzer® 8000.				
5. Scan/Enter Gas Cylinder Information (Level 1, Function S). 6. Run Tests: A. Print Test (Level1, Function P). B. ACA Test (Level 1, Function C). C. Radio Frequency Interference (RFI) Test (CMS Mode or Level 1, Function B or C; Key Radio During Test). 7. Repair and/or Maintenance Performed (if any): 8. Complete the Top Portion of the Intoxilyzer® Record (SFN50496, Form 120-G) and Place it by the Intoxilyzer® for Use. 9. File Previous Intoxilyzer® Record (SFN504096, Form 120-G) at the Intoxilyzer® Location at the Agency. 10. Send the Following to the Crime Laboratory: Completed Intoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form 104-G), Print Test, ACA Test, and RFI Test.	☑ 3. Breath Tube Heated.				
A. Print Test (Level1, Function P). B. ACA Test (Level 1, Function C). C. Radio Frequency Interference (RFI) Test (CMS Mode or Level 1, Function B or C; Key Radio During Test). 7. Repair and/or Maintenance Performed (if any): 8. Complete the Top Portion of the Intoxilyzer® Record (SFN50496, Form 120-G) and Place it by the Intoxilyzer® for Use. 9. File Previous Intoxilyzer® Record (SFN504096, Form 120-G) at the Intoxilyzer® Location at the Agency. 10. Send the Following to the Crime Laboratory: Completed Intoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form 104-G), Print Test, ACA Test, and RFI Test.	4. Enter Preliminary Data (i.e. Date, Time, DST (Y), and Location	on; Level 2, Function E).			
A. Print Test (Level1, Function P). B. ACA Test (Level 1, Function C). C. Radio Frequency Interference (RFI) Test (CMS Mode or Level 1, Function B or C; Key Radio During Test). 7. Repair and/or Maintenance Performed (if any): 8. Complete the Top Portion of the Intoxilyzer® Record (SFN50496, Form 120-G) and Place it by the Intoxilyzer® for Use. 9. File Previous Intoxilyzer® Record (SFN504096, Form 120-G) at the Intoxilyzer® Location at the Agency. 10. Send the Following to the Crime Laboratory: Completed Intoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form 104-G), Print Test, ACA Test, and RFI Test.	5. Scan/Enter Gas Cylinder Information (Level 1, Function S).				
B. ACA Test (Level 1, Function C). C. Radio Frequency Interference (RFI) Test (CMS Mode or Level 1, Function B or C; Key Radio During Test). 7. Repair and/or Maintenance Performed (if any): 8. Complete the Top Portion of the Intoxilyzer® Record (SFN50496, Form 120-G) and Place it by the Intoxilyzer® for Use. 9. File Previous Intoxilyzer® Record (SFN504096, Form 120-G) at the Intoxilyzer® Location at the Agency. 10. Send the Following to the Crime Laboratory: Completed Intoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form 104-G), Print Test, ACA Test, and RFI Test.	6. Run Tests:				
C. Radio Frequency Interference (RFI) Test (CMS Mode or Level 1, Function B or C; Key Radio During Test). 7. Repair and/or Maintenance Performed (if any): 8. Complete the Top Portion of the Intoxilyzer® Record (SFN50496, Form 120-G) and Place it by the Intoxilyzer® for Use. 9. File Previous Intoxilyzer® Record (SFN504096, Form 120-G) at the Intoxilyzer® Location at the Agency. 10. Send the Following to the Crime Laboratory: Completed Intoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form 104-G), Print Test, ACA Test, and RFI Test.	A. Print Test (Level1, Function P).				
7. Repair and/or Maintenance Performed (if any): 8. Complete the Top Portion of the Intoxilyzer® Record (SFN50496, Form 120-G) and Place it by the Intoxilyzer® for Use. 9. File Previous Intoxilyzer® Record (SFN504096, Form 120-G) at the Intoxilyzer® Location at the Agency. 10. Send the Following to the Crime Laboratory: Completed Intoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form 104-G), Print Test, ACA Test, and RFI Test.	B. ACA Test (Level 1, Function C).				
8. Complete the Top Portion of the Intoxilyzer® Record (SFN50496, Form 120-G) and Place it by the Intoxilyzer® for Use. 9. File Previous Intoxilyzer® Record (SFN504096, Form 120-G) at the Intoxilyzer® Location at the Agency. 10. Send the Following to the Crime Laboratory: Completed Intoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form 104-G), Print Test, ACA Test, and RFI Test.	C. Radio Frequency Interference (RFI) Test (CMS Mode or Level 1, Function B or C; Key Radio During Test).				
9. File Previous Intoxilyzer® Record (SFN504096, Form 120-G) at the Intoxilyzer® Location at the Agency. 10. Send the Following to the Crime Laboratory: Completed Intoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form 104-G), Print Test, ACA Test, and RFI Test.	7. Repair and/or Maintenance Performed (if any):				
10. Send the Following to the Crime Laboratory: Completed Intoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form 104-G), Print Test, ACA Test, and RFI Test.	8. Complete the Top Portion of the Intoxilyzer® Record (SFN50	0496, Form 120-G) and Place it by the	Intoxilyzer® for Use.		
— 104-G), Print Test, ACA Test, and RFI Test.					
Field Inspector Signature Date 05/10/2021	10. Send the Following to the Crime Laboratory: Completed Into 104-G), Print Test, ACA Test, and RFI Test.	oxilyzer® 8000 Installation and Repair	Checkout (SFN59281, Form		
150 nec 05/19781	Field Inspector Signature		Date		
	fee nee		05/19/2021		

Crime Laboratory Use Only

This installation has been reviewed and the instrument is approved to be used for the analysis of breath to determine alcohol concentration from the date the Field Inspector performed the installation. This record on file at the Office of Attorney General, Crime Laboratory Division, in the County of Burleigh, North Dakota, is certified to be a true and correct copy of the documents received.

Reviewed/Certified By		Certified Date
	Jealle The	5/21/21
		0/5//0/

FORM 104-G

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer Alcohol Analyzer
North Dakota Model 8000 SN 80-007098
Location = TIOG 8164.16.00 09/18
05/10/2021 20:34

******* Printer Test ********

abcdefghijklmnopqrstuvwxyz1234567890-=|
ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&*()_+?

abcdefghijklmnopqrstuvwxyz1234567890-=| ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&*()_+?

Current Instrument Setup Data Entry Mode: Enabled Start Test Sequence: DAN Display Prelim Rslt? Yes Display Third Digit? Yes Inhib Printer(Y/N)? No DABACABA Yes Yes Display Volume? No Disable On Memfull? Yes # of Print Copies? 1 Select Std (D/W/I)? Dry 0.080 Standard Value? Standard Lot #? 02621080A1 Standard Cyl #? 19 Standard Expiration? 03/05/2023 Oper No? 130977

Flow Cal. Date: 09/26/2018 Slope 684 Intercept -588446

IR Calibration Date: 09/26/2018

3um 9um

Oth Coef(*100): -40948 -15551
1st Coef(*100): 237555 134140
2nd Coef(*100): 2571 1433
H2O adj(mg/l*10k): 1097 457

****** Printer Test End *******

Operator Signature
JOSHUA NELSON

Remarks:

Form 106-I8000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer
North Dakota Model 8000
Location = TIOG
05/10/2021

Alcohol Analyzer SN 80-007098 8164.16.00 09/18 20:36

DRY CAL CHECK

Test	AC	Time
01 Room Air	0.000	20:36
02 Std. Gas	0.081	20:37
03 Room Air	0.000	20:37
04 Std. Gas	0.082	20:38
05 Room Air	0.000	20:38
06 Std. Gas	0.082	20:38
07 Room Air	0.000	20:39

Lot No = 02621080A1

Cyl No = 19

Exp Date = 03/05/2023

County = 53

Oper No. = 130977

Operator Signature JOSHUA NELSON

Remarks:

Form 106-I8000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer Alcohol Analyzer North Dakota Model 8000 SN 80-007098 Location = TIOG 8164.16.00 09/18 05/10/2021

Test	AC	Time
01 Room Air	RFI*	20:44
02 Room Air	RFI*	20:45

20:41

*Invalid Test Inhibited - RFI

Sub Name = RFI TEST, RFI TEST RFI TEST

Sub DOB = 01/01/2000

Sub Sex = Unknown Weight = NA Test = OTHCit = NA

Dr. Lic. = ND/NA

Lot No = 02621080A1

Cyl No = 19

Expiration Date = 03/05/2023

County = 53Oper No. = 130977

> Operator Signature JOSHUA NELSON

Remarks:

Form 106-I8000