

## INTOXILYZER® 8000 INSTALLATION AND REPAIR CHECKOUT

NORTH DAKOTA OFFICE OF ATTORNEY GENERAL CRIME LABORATORY DIVISION-TOXICOLOGY SECTION/BREATH ALCOHOL PROGRAM SFN 59281 (06/2018)

Serial Number	Instrument Location Socyent (a SD - Forman SACO
Reason for Install/Repair	
Install After Receiving From Crime Laboratory   Install Af	After Location Change
Other (Specify)	
Check When Done:	
1. Surge Protector Installed/Property Grounded.	
2. Telephone Line Connected to Intoxilyzer® 8000.	
3. Breath Tube Heated.	•
4. Enter Preliminary Data (i.e. Date, Time, DST (Y), and Loca	ation; Level 2, Function E).
5. Scan/Enter Gas Cylinder Information (Level 1, Function S)	).
6. Run Tests:	
A. Print Test (Level1, Function P).	
B. ACA Test (Level 1, Function C).	
C. Radio Frequency Interference (RFI) Test (CMS Mode of	or Level 1, Function B or C; Key Radio During Test).
7. Repair and/or Maintenance Performed (if any):	
8. Complete the Top Portion of the Intoxilyzer® Record (SFN	N50496, Form 120-G) and Place it by the Intoxilyzer® for Use.
9. File Previous Intoxilyzer® Record (SFN504096, Form 120-	-G) at the Intoxilyzer® Location at the Agency.
10. Send the Following to the Crime Laboratory: Completed Ir 104-G), Print Test, ACA Test, and RFI Test.	ntoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form
Field Inspector Signature	Date
7400	2//9/2014
Crime Laboratory Use Only	
	be used for the analysis of breath to determine alcohol concentration from a file at the Office of Attorney General, Crime Laboratory Division, in the copy of the documents received.
Reviewed/Certified By	Certified Date

FORM 104-G

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer Alcohol Analyzer North Dakota Model 8000 SN 80-006681 Location = SACO 8164.14.00 09/16 02/19/2019 17:38

\*\*\*\*\*\*\*\*\* Printer Test \*\*\*\*\*\*\*\*\*

abcdefghijklmnopqrstuvwxyz1234567890-=| ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&\*() +?

abcdefghijklmnopqrstuvwxyz1234567890-=| ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&\*()\_+?

Current Instrument Setup Data Entry Mode.

Start Test Sequence: DABA
Display Prelim Rslt? Yes
Display Third Digit? Yes
No Data Entry Mode: Enabled DABACABA Display Volume? No Disable On Memfull? Yes # of Print Copies? 1 Select Std (D/W/I)? Dry Standard Value? 0.080 Standard Lot #? 17618080A3 Standard Cyl #? 027 Standard Expiration? 08/05/2020 Oper No? 131081

Flow Cal. Date: 01/31/2019 Slope 611 Intercept -495195

IR Calibration Date: 01/31/2019 3um 9um -32768 133530

Oth Coef(\*100): -21843 1st Coef(\*100): 266965 2nd Coef(\*100): 1771 1342 H2O adj(mg/l\*10k): 252436

\*\*\*\*\*\*\* Printer Test End \*\*\*\*\*\*\*

Operator Signature TANNER TOUGAS

Remarks:

Form 106-I8000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer Alcohol Analyzer North Dakota Model 8000 Location = SACO 02/19/2019

SN 80-006681 8164.14.00 09/16 17:38

## DRY CAL CHECK

Test			AC	Time
01	Room	Air	0.000	17:39
02	Std.	Gas	0.078	17:39
03	Room	Air	0.000	17:40
04	Std.	Gas	0.079	17:40
05	Room	Air	0.000	17:41
06	Std.	Gas	0.079	17:41
07	Room	Air	0.000	17:41

Lot No = 17618080A3

Cyl No = 027

Exp Date = 08/05/2020

County = 41

Oper No. = 131081

Operator Signature TANNER TOUGAS

Remarks:

Form 106-I8000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer	Alcohol Analyzer
North Dakota Model 8000	SN 80-006681
Location = SACO	8164.14.00 09/16
02/19/2019	17:42

Test	AC	Time
01 Diagnostic	OK	17:43
02 Room Air	0.000	17:44
03 *Subject Test	RFI*	17:44
04 Room Air	0.000	17:45

\*Invalid Test Inhibited - RFI

Sub Name = TEST, TEST TEST

Sub DOB = 01/01/1900

Sub Sex = Male Weight = NA Test = OTH Cit = 0000000000000

Dr. Lic. = ND/TES001234

Lot No = 17618080A3Cyl No = 027

Expiration Date = 08/05/2020

County = 41 Oper No. = 131081

I followed the Approved Method and the instructions displayed by the Intoxilyzer in conducting this test.

Operator Signature TANNER TOUGAS

Remarks:

Form 106-I8000