

## INTOXILYZER® 8000 INSTALLATION AND REPAIR CHECKOUT NORTH DAKOTA OFFICE OF ATTORNEY GENERAL

CRIME LABORATORY DIVISION-TOXICOLOGY SECTION/BREATH ALCOHOL PROGRAM SFN 59281 (06/2018)

Serial Number 8 0 - 00 6 6 8 5	Instrument Location Mercer Ctu - Stanfor			
Reason for Install/Repair				
Install After Receiving From Crime Laboratory Install After	er Location Change			
A Other (Specify) Time change				
Check When Done:				
1. Surge Protector Installed/Property Grounded.				
2. Telephone Line Connected to Intoxilyzer® 8000.				
☐ 3. Breath Tube Heated.				
Enter Preliminary Data (i.e. Date, Time, DST (Y), and Location; Level 2, Function E).				
5. Scan/Enter Gas Cylinder Information (Level 1, Function S).				
6. Run Tests:				
A. Print Test (Level1, Function P).				
B. ACA Test (Level 1, Function C).				
C. Radio Frequency Interference (RFI) Test (CMS Mode or Level 1, Function B or C; Key Radio During Test).				
Tr. Repair and/or Maintenance Performed (if any): Changed Time				
Complete the Top Portion of the Intoxilyzer® Record (SFN50496, Form 120-G) and Place it by the Intoxilyzer® for Use.				
☐ 9. File Previous Intoxilyzer® Record (SFN504096, Form 120-G	at the Intoxilyzer® Location at the Agency.			
<ol> <li>Send the Following to the Crime Laboratory: Completed Into 104-G), Print Test, ACA Test, and RFI Test.</li> </ol>	oxilyzer® 8000 Installation and Repair Checkout (SFN5	i9281, Form		
Field Inspector Signature	Date .			
File	3/18/	19		
	7			

Crime Laboratory Use Only

This installation has been reviewed and the instrument is approved to be used for the analysis of breath to determine alcohol concentration from the date the Field Inspector performed the installation. This record on file at the Office of Attorney General, Crime Laboratory Division, in the County of Burleigh, North Dakota, is certified to be a true and correct copy of the documents received.

Reviewed/Certified By	Charlester	Certified Date 3/22/19
	0	

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501 CMI, Inc. Intoxilyzer Alcohol Analyzer North Dakota Model 8000 SN 80-006685 Location = STAT 8164.14.00 09/16 03/18/2019 18:16 \*\*\*\*\*\*\*\*\*\*\*\*\* Printer Test \*\*\*\*\*\*\*\*\*\*\*\*\*\*\* abcdefghijklmnopqrstuvwxyz1234567890-=| ABCDEFGHIJKLMNOPORSTUVWXYZ!@#\$%^&\*()\_+? abcdefghijklmnopqrstuvwxyz1234567890-= ABCDEFGHIJKLMNOPQRSTUVWXYZ !@#\$%^&\*()\_+? Current Instrument Setup Data Entry Mode: Enabled Start Test Sequence: DABACABA Display Prelim Rslt? Yes Display Third Digit? Yes Inhib Printer(Y/N)? No Display Volume? No Disable On Memfull? Yes # of Print Copies? 1 Select Std (D/W/I)? Dry Standard Value? 0.080 Standard Lot #? 17618080A3 Standard Cyl #? 69 Standard Expiration? 08/05/2020 Oper No? 120906 Flow Cal. Date: 09/06/2016 Slope 705 Intercept -687370 IR Calibration Date: 09/06/2016 3um 9ur 9um 0th Coef(\*100):-141551st Coef(\*100):2714362nd Coef(\*100):2016 -22915 135296 1251 H2O adj(mg/l\*10k): 372 505

\*\*\*\*\*\*\*\*\*\* Printer Test End \*\*\*\*\*\*\*\*\*\*

Operator Signature PAMELA PEHL

Remarks:

Form 106-18000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

North Dakota Model 8000	Alcohol Analyzer SN 80-006685
Location = STAT	8164.14.00 09/16
03/18/2019	18:16

	DRY CAL CHECK	
Test	AC	Time
01 Room Air 02 Std. Gas 03 Room Air 04 Std. Gas 05 Room Air 06 Std. Gas 07 Room Air	0.000 0.082 0.000 0.081 0.000 0.082 0.000	18:17 18:17 18:18 18:18 18:19 18:19 18:20

Lot No = 17618080A3 Cyl No = 69 Exp Date = 08/05/2020 County = 29 Op

Oper No. = 120906

Operator Signature PAMELA PEHL

Remarks:

Form 106-18000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. IntoxilyzerAlcohol AnalyzerNorth Dakota Model 8000SN 80-006685Location = STAT8164.14.00 09/1603/18/201918:20

DRY CAL	CHECK	
Test	AC	Time
01 Room Air 02 Room Air	RFI* RFI*	18:21 18:21
*Invalid Test Inhibited - RFI		
Lot No = 17618080A3 Cyl No = 69 Exp Date = 08/05/2020 County = 29	Oper No.	= 120906

Operator Signature PAMELA PEHL

Remarks:

Form 106-18000