

INTOXILYZER® 8000 INSTALLATION AND REPAIR CHECKOUT NORTH DAKOTA OFFICE OF ATTORNEY GENERAL CRIME LABORATORY DIVISION-TOXICOLOGY SECTION/BREATH ALCOHOL PROGRAM SFN 59281 (06/2018)

Serial Number 80-006691	Instrument Location Kenmare Police Dept.			
Reason for Install/Repair				
🔲 Install After Receiving From Crime Laboratory 🛛 Install After Location Change				
A Other (Specify) New Gas Cylinder	Installation			
Check When Done:				
1. Surge Protector Installed/Property Grounded.				
2. Telephone Line Connected to Intoxilyzer® 8000.				
 ☑ 3. Breath Tube Heated. 				
4. Enter Preliminary Data (i.e. Date, Time, DST (Y), and Location	on; Level 2, Function E).			
5. Scan/Enter Gas Cylinder Information (Level 1, Function S).				
, G. Run Tests:				
A. Print Test (Level1, Function P).				
B. ACA Test (Level 1, Function C).				
C. Radio Frequency Interference (RFI) Test (CMS Mode or I	Level 1, Function B or C; Key Radio During Test).			
7, Repair and/or Maintenance Performed (if any):	Cylinder Installation			
8. Complete the Top Portion of the Intoxilyzer® Record (SFN50	0496, Form 120-G) and Place it by the Intoxilyzer® for Use.			
9. File Previous Intoxilyzer® Record (SFN504096, Form 120-G) at the Intoxilyzer® Location at the Agency.				
10. Send the Following to the Crime Laboratory: Completed Intoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form 104-G), Print Test, ACA Test, and RFI Test.				
Field Inspector Signature	Date 4/10/2021			

Crime Laboratory Use Only

This installation has been reviewed and the instrument is approved to be used for the analysis of breath to determine alcohol concentration from the date the Field Inspector performed the installation. This record on file at the Office of Attorney General, Crime Laboratory Division, in the County of Burleigh, North Dakota, is certified to be a true and correct copy of the documents received.

	1	
Reviewed/Certified By	Charles Et	Certified Date 4,23.202

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. IntoxilyzerAlcohol AnalyzerNorth Dakota Model 8000SN 80-006691Location = KMPD8164.14.00 09/1604/10/202120:26

abcdefghijklmnopqrstuvwxyz1234567890-=| ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&*() +?

abcdefghijklmnopqrstuvwxyz1234567890-=| ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&*() +?

Current Instrument	Setup		
Data Entry Mode:		Enabled	
Start Test Sequence	:	DABACABA	
Display Prelim Rslt	?	Yes	
Display Third Digit?		Yes	
Inhib Printer(Y/N)?		No	
Display Volume?		No	
Disable On Memfull?		Yes	
# of Print Copies?		1	
Select Std (D/W/I)?		Dry	
Standard Value?		0.080	
Standard Lot #?		02621080A1	
Standard Cyl #?		030	
Standard Expiration	?	03/05/2023	
Oper No?		132664	
Flow Cal. Date:		08/28/2018	
Slope		699	
Intercept		-660610	
IR Calibration Date	:	08/28/2018	
	3um	9um	
	-9426	-20764	
1st Coef(*100):	258193	134855	
2nd Coef(*100):	3532	1465	

547

H2O adj(mg/l*10k): 408

Operator Signature CHRISTOPHER ALMLIE

Remarks:

Form 106-I8000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. IntoxilyzerAlcohol AnalyzerNorth Dakota Model 8000SN 80-006691Location = KMPD8164.14.00 09/1604/10/202120:26

	DRY CAL CHECK	
Test	AC	Time
01 Room Air	0.000	20:27
02 Std. Gas	0.082	20:27
03 Room Air	0.000	20:28
04 Std. Gas	0.082	20:28
05 Room Air	0.000	20:29
06 Std. Gas	0.082	20:29
07 Room Air	0.000	20:29

Lot No = 02621080A1 Cyl No = 030 Exp Date = 03/05/2023 County = 51

Oper No. = 132664

2 1 1

Operator Signature CHRISTOPHER ALMLIE

Remarks:

Form 106-18000

.

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501 CMI, Inc. Intoxilyzer Alcohol Analyzer North Dakota Model 8000 SN 80-006691 Location = KMPD 8164.14.00 09/16 04/10/2021 20:30 Test AC Time 01 Room Air RFI* 20:31 02 Room Air 0.000 20:32 *Invalid Test Inhibited - RFI Sub Name = TEST, TEST TEST Sub DOB = 04/10/1991Sub Sex = Unknown Weight = NA Test = OTHCit = NADr. Lic. = ND/NA Lot No = 02621080A1Cyl No = 030Expiration Date = 03/05/2023County = 51Oper No. = 132664

Operator Signature CHRISTOPHER ALMLIE

Remarks:

Form 106-I8000

,