

INTOXILYZER® 8000 INSTALLATION AND REPAIR CHECKOUT

NORTH DAKOTA OFFICE OF ATTORNEY GENERAL CRIME LABORATORY DIVISION-TOXICOLOGY SECTION/BREATH ALCOHOL PROGRAM SFN 59281 (06/2018)

Serial Number	Instrument Location
80 - 00 668 7 Reason for Install/Repair	Powers Lake PD
	ther Legation Change
+ • • • • • • • • • • • • • • • • • • •	fter Location Change
Other (Specify)	
Check When Done:	
1. Surge Protector Installed/Property Grounded.	
2. Telephone Line Connected to Intoxilyzer® 8000.	
3. Breath Tube Heated.	
4. Enter Preliminary Data (i.e. Date, Time, DST (Y), and Loca	ition; Level 2, Function E).
5. Scan/Enter Gas Cylinder Information (Level 1, Function S).	
6. Run Tests:	
A. Print Test (Level1, Function P).	
B. ACA Test (Level 1, Function C).	
C. Radio Frequency Interference (RFI) Test (CMS Mode o	or Level 1, Function B or C; Key Radio During Test).
7. Repair and/or Maintenance Performed (if any):	
8. Complete the Top Portion of the Intoxilyzer® Record (SFN5	50496, Form 120-G) and Place it by the Intoxilyzer® for Use.
9. File Previous Intoxilyzer® Record (SFN504096, Form 120-0	G) at the Intoxilyzer® Location at the Agency.
10. Send the Following to the Crime Laboratory: Completed Int 104-G), Print Test, ACA Test, and RFI Test.	toxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form
Field Inspector Signature Why the Whole Company of the Company of	07MAY21
Crime Laboratory Use Only	
	be used for the analysis of breath to determine alcohol concentration from
the date the Field Inspector performed the installation. This record on f County of Burleigh, North Dakota, is certified to be a true and correct county.	file at the Office of Attorney General, Crime Laboratory Division, in the

FORM 104-G

Reviewed/Certified By

Certified Date

5.17.21

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer Alcohol Analyzer
North Dakota Model 8000 SN 80-006687
Location = PLPD 8164.14.00 09/16
05/07/2021 20:07

****** Printer Test *******

abcdefghijklmnopqrstuvwxyz1234567890-= |
ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&*() +?

abcdefghijklmnopqrstuvwxyz1234567890-=|
ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&*() +?

Current Instrument Setup

Data Entry Mode: Enabled Start Test Sequence:
Display Prelim Rslt?
Display Third Digit? DABACABA Yes Yes Inhib Printer(Y/N)? No Display Volume? No Disable On Memfull?
of Print Copies? Yes # of Print Copies? 1 Select Std (D/W/I)? Dry Standard Value? 0.080 Standard Lot #? Standard Cyl #? 02621080A1 28 Standard Expiration? 03/05/2023 Oper No? 132720

Flow Cal. Date: 10/05/2018 Slope 696

Intercept -609977

IR Calibration Date: 10/05/2018
3um 9um

Oth Coef(*100): -11478 -18771
1st Coef(*100): 255256 132135
2nd Coef(*100): 4432 1676
H2O adj(mg/l*10k): 604 575

****** Printer Test End *******

operator Signature BRYTON ALLARD

Remarks:

Form 106-I8000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer
North Dakota Model 8000
Location = PLPD
05/07/2021

Alcohol Analyzer SN 80-006687 8164.14.00 09/16 20:08

DRY CAL CHECK

Test	AC	Time
01 Room Air	0.000	20:09
02 Std. Gas	0.082	20:09
03 Room Air	0.000	20:10
04 Std. Gas	0.082	20:10
05 Room Air	0.000	20:11
06 Std. Gas	0.081	20:11
07 Room Air	0.000	20:11

Lot No = 02621080A1

Cyl No = 28

Exp Date = 03/05/2023

County = 07

Oper No. = 132720

perator Signature BRYTON ALLARD

Remarks:

Form 106-I8000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

SN 80-006687

20:14

CMI, Inc. Intoxilyzer Alcohol Analyzer North Dakota Model 8000 Location = PLPD 8164.14.00 09/16 05/07/2021

Test			AC	Time
01	Room	Air	RFI*	20:15
02	Room	Air	RFI*	20:16

*Invalid Test Inhibited - RFI

Sub Name = TEST, TEST TEST

Sub DOB = 01/01/1990

Sub Sex = MaleWeight = 180Test = OTH Cit = NA

Dr. Lic. = ND/NALot No = 02621080A1

Cyl No = 28

Expiration Date = 03/05/2023

County = 07Oper No. = 132720

> Operator Signature BRYTON ALLARD

Remarks:

Form 106-I8000