

## INTOXILYZER® 8000 INSTALLATION AND REPAIR CHECKOUT

NORTH DAKOTA OFFICE OF ATTORNEY GENERAL CRIME LABORATORY DIVISION-TOXICOLOGY SECTION/BREATH ALCOHOL PROGRAM SFN 59281 (06/2018)

Serial Number 80 - CO (485  Reason for Install/Repair	Instrument Location
·	- Lostell Afficial coeffice Observe
	Install After Location Change
Other (Specify)	
Check When Done:	
1. Surge Protector Installed/Property Grounded.	
2. Telephone Line Connected to Intoxilyzer® 800	00.
🔉 3. Breath Tube Heated.	
🔀 4. Enter Preliminary Data (i.e. Date, Time, DST (	Y), and Location; Level 2, Function E).
5. Scan/Enter Gas Cylinder Information (Level 1,	Function S).
🙇 6. Run Tests:	
A. Print Test (Level1, Function P).	
☑ B. ACA Test (Level 1, Function C).	
The state of the s	CMS Mode or Level 1, Function B or C; Key Radio During Test).
7. Repair and/or Maintenance Performed (if any):	: Nane
★ 8. Complete the Top Portion of the Intoxilyzer® R	Record (SFN50496, Form 120-G) and Place it by the Intoxilyzer® for Use.
9. File Previous Intoxilyzer® Record (SFN504096	6, Form 120-G) at the Intoxilyzer® Location at the Agency.
10. Send the Following to the Crime Laboratory: 0 104-G), Print Test, ACA Test, and RFI Test.	Completed Intoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form
Field Inspector Signature	Date 5/19/21
Crime Laboratory Use Only	
	approved to be used for the analysis of breath to determine alcohol concentration fror his record on file at the Office of Attorney General, Crime Laboratory Division, in the

Reviewed/Certified By

5/27/202

FORM 104-G

County of Burleigh, North Dakota, is certified to be a true and correct copy of the documents received.

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer Alcohol Analyzer
North Dakota Model 8000 SN 80-006685
Location = GARR 8164.14.00 09/16
05/19/2021 18:47

\*\*\*\*\*\*\*\* Printer Test \*\*\*\*\*\*\*\*

abcdefghijklmnopqrstuvwxyz1234567890-=|
ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&\*() +?

abcdefghijklmnopqrstuvwxyz1234567890-=|
ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&\*() +?

Current Instrument Setup

Data Entry Mode: Enabled Start Test Sequence: Display Prelim Rslt? DABACABA Yes Display Third Digit? Yes Inhib Printer(Y/N)? No Display Volume? No Disable On Memfull? Yes # of Print Copies? Select Std (D/W/I)? Dry Standard Value? 0.080 Standard Lot #? Standard Cyl #? 24119080A1 21 Standard Expiration? 11/05/2021 Oper No? 100724

Flow Cal. Date: 09/06/2016 Slope 705 Intercept -687370

IR Calibration Date: 09/06/2016 3um 9um

Oth Coef(\*100): -14155 -22915
1st Coef(\*100): 271436 135296
2nd Coef(\*100): 2016 1251
H2O adj(mg/l\*10k): 372 505

\*\*\*\*\*\*\* Printer Test End \*\*\*\*\*\*\*\*

Operator Signature CODY MEADOWS

Remarks:

Form 106-I8000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer Alcohol Analyzer North Dakota Model 8000 Location = GARR 05/19/2021

SN 80-006685 8164.14.00 09/16 18:56

## DRY CAL CHECK

Test	AC	Time
01 Room Air	0.000	18:57
02 Std. Gas	0.082	18:57
03 Room Air	0.000	18:57
04 Std. Gas	0.082	18:58
05 Room Air	0.000	18:58
06 Std. Gas	0.082	18:59
07 Room Air	0.000	18:59

Lot No = 24119080A1

Cyl No = 21

Exp Date = 11/05/2021

County = 28

Oper No. = 100724

Operator Signature CODY MEADOWS

Remarks:

Form 106-I8000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer
North Dakota Model 8000
Location = GARR
05/19/2021

Test	AC	Time
01 Room Air	RFI*	19:01
02 Room Air	0.000	19:02

\*Invalid Test Inhibited - RFI

Sub Name = TEST, TESTER T

Sub DOB = 01/01/2001 Sub Sex = Male

Sub Sex = Male Weight = 230 Test = DUI Cit = 1234567

Dr. Lic. = ND/1234567Lot No = 24119080A1

Cyl No = 21

Expiration Date = 11/05/2021

County = 28

Oper No. = 100724

Alcohol Analyzer

8164.14.00 09/16

SN 80-006685

19:00

Operator Signature CODY MEADOWS

Remarks:

Form 106-I8000