

INTOXILYZER® 8000 INSTALLATION AND REPAIR CHECKOUT NORTH DAKOTA OFFICE OF ATTORNEY GENERAL

CRIME LABORATORY DIVISION-TOXICOLOGY SECTION/BREATH ALCOHOL PROGRAM SFN 59281 (06/2018)

Serial Number 80-004942	Instrument Location				
Reason for Install/Repair					
Install After Receiving From Crime Laboratory					
Other (Specify)					
Check When Done:					
1. Surge Protector Installed/Property Grounded.					
2. Telephone Line Connected to Intoxilyzer® 8000.					
3. Breath Tube Heated					
4. Enter Preliminary Data (i.e. Date, Time, DST (Y), and Location; Level 2, Function E).					
5. Scan/Enter Gas Cylinder Information (Level 1, Function S).					
☐ 6. Run Tests:					
A. Print Test (Level1, Function P).					
B. ACA Test (Level 1, Function C).					
C. Radio Frequency Interference (RFI) Test (CMS Mode or Level 1, Function B or C; Key Radio During Test).					
7. Repair and/or Maintenance Performed (if any):					
S. Complete the Top Portion of the Intoxilyzer® Record (SFN50496, Form 120-G) and Place it by the Intoxilyzer® for Use.					
9. File Previous Intoxilyzer® Record (SFN504096, Form 120-G) at the Intoxilyzer® Location at the Agency.					
 Send the Following to the Crime Laboratory: Completed Int 104-G), Print Test, ACA Test, and RFI Test. 	toxilyzer® 8000 Installation and Repair C	heckout (SFN59281, Form			
Field Instanting		Date			
Field Inspector Signature		4/26/21			

Crime Laboratory Use Only

This installation has been reviewed and the instrument is approved to be used for the analysis of breath to determine alcohol concentration from the date the Field Inspector performed the installation. This record on file at the Office of Attorney General, Crime Laboratory Division, in the County of Burleigh, North Dakota, is certified to be a true and correct copy of the documents received.

Reviewed/Certified By	Charlack	Certified Date 4.2.8-2.1
		,

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501 Alcohol Analyzer CMI, Inc. Intoxilyzer North Dakota Model 8000 SN 80-004942 8164.14.00 09/16 Location = STAT17:59 04/26/2021 ************* Printer Test ************** abcdefghijklmnopqrstuvwxyz1234567890-=| ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&*() +? abcdefghijklmnopqrstuvwxyz1234567890-= ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&*()_+? Current Instrument Setup Enabled Data Entry Mode: Start Test Sequence: DABACABA Display Prelim Rslt? Yes Display Third Digit? Yes No Inhib Printer(Y/N)? Display Volume? No Disable On Memfull? Yes 1 # of Print Copies? Dry Select Std (D/W/I)? 0.080 Standard Value? 05620080A1 Standard Lot #? Standard Cyl #? 31 Standard Expiration? 04/05/2022 120906 Oper No? 05/25/2018 Flow Cal. Date: 626 Slope -548004 Intercept IR Calibration Date: 05/25/2018 9um 3um ______ -10942 0th Coef(*100): -13713 1st Coef(*100):2556542nd Coef(*100):3705 132286 1469 H2O adj(mg/l*10k): 481 462

Operator Signature PAMELA PEHL

Remarks:

Form 106-18000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. IntoxilyzerAlcohol AnalyzerNorth Dakota Model 8000SN 80-004942Location = STAT8164.14.00 09/1604/26/202118:00

DRY CAL CHECK

Test	AC	Time
01 Room Air 02 Std. Gas 03 Room Air 04 Std. Gas 05 Room Air 06 Std. Gas 07 Room Air	0.000 0.083 0.000 0.083 0.000 0.083 0.000	18:00 18:01 18:01 18:02 18:02 18:02 18:02 18:03

Operator Signature PAMELA PEHL

Remarks:

Form 106-18000

2

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. IntoxilyzerAlcohol AnalyzerNorth Dakota Model 8000SN 80-004942Location = STAT8164.14.00 09/1604/26/202118:03

	DRY CAL	CHECK			
Test		AC	Time		
01 Room Air		0.000	18:04 18:04		
02 Std. Gas 03 Room Air		0.002	18:05		
04 Std. Gas		0.083	18:05		
05 Room Air		RFI*	18:05		
06 Room Air		RFI*	18:06		
*Invalid Test Inhibited - RFI Lot No = 05620080A1 Cyl No = 31 Exp Date = $04/05/2022$ County = 29 Oper No. = 120906					
PPehl					
Operator Signature					

PAMELA PEHL

Remarks:

Form 106-18000

á

,