

ETHANOL GAS STANDARD CYLINDER REPORT

NORTH DAKOTA OFFICE OF ATTORNEY GENERAL CRIME LABORATORY DIVISION-TOXICOLOGY SECTION/BREATH ALCOHOL PROGRAM SFN 59282 (08/2018)

| Chemical Test Operator Name (Print) Trevor K. Bergerson | | | | | |
|--|-----------------------|-------------------------------------|--------------------------------|--|--|
| Location BOPD | | Intoxilyzer® Serial Nu 80 - 0070 | imber 93 | | |
| Gas Lot Number 34921080A1 | Gas Cylinder Number | | Gas Expiration Date 02/05/2024 | | |
| Check When Done: | | | | | |
| 1. Scan/Enter Gas Cylinder Information (Level 1, Function S). | | | | | |
| 2. Perform an ACA Test (Level 1, Function C). | | | | | |
| Write in the ACA Test Results (Reported to 3 Digits, Ex. 0.081). | | | | | |
| A. 0.080 AC | | | | | |
| B. 0.080 AC | | | | | |
| c. 0. 080 AC | | | | | |
| √3. Complete the Top Portion of the Intoxilyzer® Record (SFN50496, Form 120-G) and Place it by the Intoxilyzer® for Use. | | | | | |
| 4. File Previous Intoxilyzer® Record (SFN50496, Form 120-G) at the Intoxilyzer® Location at the Agency. | | | | | |
| 5. Send the Following to the Crime Labor | oratory: | | | | |
| A. Ethanol Gas Standard Cylinder R B. ACA Test Record. | eport (SFN59282, Form | n 105-G). | | | |
| Chemical Test Operator Signature | | | Date, | | |
| I Box | | | 3/3/2023 | | |
| Reviewed By (Crime Laboratory Use Only) | | | Date | | |

ObMar2023

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer
North Dakota Model 8000
Location = BOPD
03/03/2023

Alcohol Analyzer SN 80-007093 8164.16.00 09/18 23:35

DRY CAL CHECK

| Test | AC | Time |
|-------------|-------|-------|
| 01 Room Air | 0.000 | 23:35 |
| 02 Std. Gas | 0.080 | 23:36 |
| 03 Room Air | 0.000 | 23:36 |
| 04 Std. Gas | 0.080 | 23:36 |
| 05 Room Air | 0.000 | 23:37 |
| 06 Std. Gas | 0.080 | 23:37 |
| 07 Room Air | 0.000 | 23:38 |

Lot No = 34921080A1

Cyl No = 44

Exp Date = 02/05/2024

County = 06

Oper No. = 130538

Operator Signature TREVOR BERGERSON

Remarks:

Form 106-I8000