

INTOXILYZER® 8000 INSTALLATION AND REPAIR CHECKOUT NORTH DAKOTA OFFICE OF ATTORNEY GENERAL CRIME LABORATORY DIVISION-TOXICOLOGY SECTION/BREATH ALCOHOL PROGRAM SFN 59281 (06/2018)

Serial Number 90-006684	Instrument Location			
Reason for Install/Repair				
🖄 Install After Receiving From Crime Laboratory 🛛 🗌 Install After Location Change				
Dether (Specify) Annual Inspection at Chine Laboratory				
Check When Done:	0			
1. Surge Protector Installed/Property Grounded.				
2. Telephone Line Connected to Intoxilyzer® 8000.				
3. Breath Tube Heated.				
4. Enter Preliminary Data (i.e. Date, Time, DST (Y), and Location; Level 2, Function E).				
5. Scan/Enter Gas Cylinder Information (Level 1, Function S).				
6. Run Tests:				
A. Print Test (Level1, Function P).				
B. ACA Test (Level 1, Function C).				
C. Radio Frequency Interference (RFI) Test (CMS Mode or Level 1, Function B or C; Key Radio During Test).				
7. Repair and/or Maintenance Performed (if any):				
8. Complete the Top Portion of the Intoxilyzer® Record (SFN50496, Form 120-G) and Place it by the Intoxilyzer® for Use.				
9. File Previous Intoxilyzer® Record (SFN504096, Form 120-G) at the Intoxilyzer® Location at the Agency.				
 Send the Following to the Crime Laboratory: Completed Intoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form 104-G), Print Test, ACA Test, and RFI Test. 				
Field Inspector Signature		Date		

Crime Laboratory Use Only

This installation has been reviewed and the instrument is approved to be used for the analysis of breath to determine alcohol concentration from the date the Field Inspector performed the installation. This record on file at the Office of Attorney General, Crime Laboratory Division, in the County of Burleigh, North Dakota, is certified to be a true and correct copy of the documents received.

Reviewed/Certified By	An	nal	Certified Date 19May2023

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501 CMI, Inc. Intoxilyzer Alcohol Analyzer North Dakota Model 8000 SN 80-006684 Location = WFPD 8164.14.00 09/16 05/17/2023 22:24 ************ Printer Test ************ abcdefghijklmnopqrstuvwxyz1234567890-= ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&*() +? abcdefghijklmnopqrstuvwxyz1234567890-=| ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&*() +? Current Instrument Setup Data Entry Mode: Enabled Start Test Sequence: DABA Display Prelim Rslt? Yes DABACABA Display Third Digit? Yes Inhib Printer(Y/N)? No Display Volume? No Disable On Memfull? Yes # of Print Copies? 1 Select Std (D/W/I)? Dry 0.080 Standard Value? Standard Lot #? Standard Cyl #? 26021080A1 2 Standard Expiration? 10/05/2023 Oper No? 121019 09/06/2016 Flow Cal. Date: Slope 709 Intercept -725441 IR Calibration Date: 09/06/2016 3um 9um _____ 0th Coef(*100):-160131st Coef(*100):2564312nd Coef(*100):2904 -23467 135731 1268 H2O adj(mg/l*10k): 553 514

Operator Signature RYAN HASKELL

Remarks:

Form 106-18000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer	Alcohol Analyzer
North Dakota Model 8000	SN 80-006684
Location = WFPD	8164.14.00 09/16
05/17/2023	22:24

CHECK]
AC	-
	Time
0.000 0.080 0.000 0.080	22:25 22:25 22:26 22:26 22:27 22:27 22:27
	0.000 0.080

Lot No = 26021080A1 Cyl No = 2 Exp Date = 10/05/2023 County = 09 Oper No.

Oper No. = 121019

Operator Signature RYAN HASKELL

Remarks:

Form 106-18000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. IntoxilyzerAlcohol AnalyzerNorth Dakota Model 8000SN 80-006684Location = WFPD8164.14.00 09/1605/17/202322:30

DRY	CAL CHECK			
Test	AC	Time		
01 Room Air 02 Room Air	RFI* 0.000	22:30 22:31		
*Invalid Test Inhibited - RFI				
Lot No = 260210802 Cyl No = 2 Exp Date = 10/05/2				

Oper No. = 121019

Operator Signature RYAN HASKELL

Remarks:

County = 09

Form 106-18000

.