

INTOXILYZER® 8000 INSTALLATION AND REPAIR CHECKOUT

NORTH DAKOTA OFFICE OF ATTORNEY GENERAL CRIME LABORATORY DIVISION-TOXICOLOGY SECTION/BREATH ALCOHOL PROGRAM SFN 59281 (06/2018)

Serial Number 80 - 00 6 5 1 2	Instrument Location Carring by	PD (CARR)		
Reason for Install/Repair	J			
☐ Install After Receiving From Crime Laboratory ☐ Install After	er Location Change			
Other (Specify) Annual inspection from	ND Crine Lab			
Check When Done:				
1. Surge Protector Installed/Property Grounded.				
2. Telephone Line Connected to Intoxilyzer® 8000.				
√ 3. Breath Tube Heated.				
4. Enter Preliminary Data (i.e. Date, Time, DST (Y), and Location	on; Level 2, Function E).			
5. Scan/Enter Gas Cylinder Information (Level 1, Function S).				
6. Run Tests:				
A. Print Test (Level1, Function P).				
B. ACA Test (Level 1, Function C).				
C. Radio Frequency Interference (RFI) Test (CMS Mode or	Level 1, Function B or C; Key Radio Du	ring Test).		
7. Repair and/or Maintenance Performed (if any):	/A			
8. Complete the Top Portion of the Intoxilyzer® Record (SFN50	0496, Form 120-G) and Place it by the Ir	ntoxilyzer® for Use.		
9. File Previous Intoxilyzer® Record (SFN504096, Form 120-G	i) at the Intoxilyzer® Location at the Age	ncy.		
10. Send the Following to the Crime Laboratory: Completed Into 104-G), Print Test, ACA Test, and RFI Test.	oxilyzer® 8000 Installation and Repair C	heckout (SFN59281, Form		
Field Inspector Signature	1621	Date 6/6/2023		
Crime Laboratory Use Only				
This installation has been reviewed and the instrument is approved to be the date the Field Inspector performed the installation. This record on fill County of Burleigh, North Dakota, is certified to be a true and correct co	le at the Office of Attorney General, Crin	mine alcohol concentration from ne Laboratory Division, in the		
Reviewed/Certified By		Certified Date 12June2023		

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer Alcohol Analyzer North Dakota Model 8000 SN 80-006512 Location = CARR 8164.14.00 09/16 06/06/2023 17:35

******* Printer Test ********

abcdefghijklmnopgrstuvwxyz1234567890-=| ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&*() +?

abcdefghijklmnopqrstuvwxyz1234567890-=| ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&*() +?

Current Instrument Setup Data Entry Mode: Enabled Start Test Sequence: Display Prelim Rslt? DABACABA Yes Display Third Digit? Yes Inhib Printer(Y/N)? No Display Volume? No Disable On Memfull? Yes # of Print Copies? 1 Select Std (D/W/I)? Dry Standard Value? 0.080 Standard Lot #? 01923080A3 Standard Cyl #? 25 Standard Expiration? 02/05/2025 Oper No? 131530

Flow Cal. Date: 08/20/2015 Slope 680 Intercept -660856

IR Calibration Date: 08/21/2015 3um 9um Oth Coef(*100): -23051 1st Coef(*100): 266836 2nd Coef(*100): 3974 -19261137135

1466 H20 adj (mg/l*10k): 785487

******* Printer Test End *******

Operator Signature

CHRISTOPHER ORMISTON

Remarks:

Form 106-I8000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer North Dakota Model 8000 Location = CARR 06/06/2023 Alcohol Analyzer SN 80-006512 8164.14.00 09/16 17:36

DRY CAL CHECK

Test	AC	Time
01 Room Air	0.000	17:37
02 Std. Gas	0.081	17:37
03 Room Air	0.000	17:38
04 Std. Gas	0.080	17:38
05 Room Air	0.000	17:39
06 Std. Gas	0.080	17:39
07 Room Air	0.000	17:39

Lot No = 01923080A3

Cyl No = 25

Exp Date = 02/05/2025

County = 16

Oper No. = 131530

Operator Signature CHRISTOPHER ORMISTON

Remarks:

Form 106-I8000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer Alcohol Analyzer North Dakota Model 8000 Location = CARR 06/06/2023

SN 80-006512 8164.14.00 09/16 17:43

Test	AC	Time
01 Room 02 Room	RFI*	17:44 17:44

*Invalid Test Inhibited - RFI

Sub Name = ORMISTON, CHRISTOPHER NEAL

Sub DOB = 08/17/1989

Sub Sex = Male

Weight = 175

Test = OTH

Cit = 00000000

Dr. Lic. = ND/SIL891627

Lot No = 01923080A3

Cyl No = 25

Expiration Date = 02/05/2025

County = 16

Oper No. = 131530

Operator Signature CHRISTOPHER ORMISTON

Remarks:

Form 106-I8000