

## INTOXILYZER® 8000 INSTALLATION AND REPAIR CHECKOUT

NORTH DAKOTA OFFICE OF ATTORNEY GENERAL CRIME LABORATORY DIVISION-TOXICOLOGY SECTION/BREATH ALCOHOL PROGRAM SFN 59281 (06/2018)

Serial Number ZO-004956 Instrument Location COOP						
Reason for Install/Repair						
🗌 Install After Receiving From Crime Laboratory 🔄 Install After Location Change						
Ø Other (Specify) Install after machine unplugged						
Check When Done:						
1. Surge Protector Installed/Property Grounded.						
2. Telephone Line Connected to Intoxilyzer® 8000.						
3. Breath Tube Heated.						
4. Enter Preliminary Data (i.e. Date, Time, DST (Y), and Location; Level 2, Function E).						
5. Scan/Enter Gas Cylinder Information (Level 1, Function S).						
🗹 6. Run Tests:						
A. Print Test (Level1, Function P).						
B. ACA Test (Level 1, Function C).						
C. Radio Frequency Interference (RFI) Test (CMS Mode or Level 1, Function B or C; Key Radio During Test).						
7. Repair and/or Maintenance Performed (if any):						
8. Complete the Top Portion of the Intoxilyzer® Record (SFN50496, Form 120-G) and Place it by the Intoxilyzer® for Use.						
9. File Previous Intoxilyzer® Record (SFN504096, Form 120-G) at the Intoxilyzer® Location at the Agency.						
10. Send the Following to the Crime Laboratory: Completed Intoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form 104-G), Print Test, ACA Test, and RFI Test.						
ield Inspector Signeture Date 12/7/23						
rime Laboratory Use Only						

This installation has been reviewed and the instrument is approved to be used for the analysis of breath to determine alcohol concentration from the date the Field Inspector performed the installation. This record on file at the Office of Attorney General, Crime Laboratory Division, in the County of Burleigh, North Dakota, is certified to be a true and correct copy of the documents received.

	$\bigcirc$		
Reviewed/Certified By	An	Mall	Certified Date 08Dec2023

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501 CMI, Inc. Intoxilyzer Alcohol Analyzer North Dakota Model 8000 SN 80-004956 Location = COOP 8164.14.00 09/16 12/05/2023 13:32 \*\*\*\*\*\*\*\*\*\*\* Printer Test \*\*\*\*\*\*\*\*\*\*\*\*\*\*\*\* abcdefghijklmnopqrstuvwxyz1234567890-=| ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&\*()\_+? abcdefghijklmnopqrstuvwxyz1234567890-=| ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&\*() +? Current Instrument Setup Data Entry Mode: Enabled Start Test Sequence: DABACABA Display Prelim Rslt? · Yes Display Third Digit? Yes Inhib Printer(Y/N)? No Display Volume? · No Disable On Memfull? Yes # of Print Copies? 1 Select Std (D/W/I)? Dry Standard Value? 0.080 Standard Lot #? Standard Cyl #? 14323080A1 70 06/05/2025 Standard Expiration? Oper No? 130095 Flow Cal. Date: 06/13/2019 Slope 606 Intercept -586035 IR Calibration Date: 06/13/2019 3um 9um 0th Coef(\*100):-199861st Coef(\*100):2632892nd Coef(\*100):2309 -21891 136002 1332 H2O adj(mg/l\*10k): 544 502

\*\*\*\*\*\*\*\*\*\* Printer Test End \*\*\*\*\*\*\*\*\*\*

Operator Signature NATHAN MORTEN

Remarks:

Form 106-18000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. IntoxilyzerAlcohol AnalyzerNorth Dakota Model 8000SN 80-004956Location = COOP8164.14.00 09/1612/05/202313:33

			DRY CAL CHECK	
Te	est		AC	Time
01	Room	Air	0.000	13:34
02	std.	Gas	0.081	13:34
03	Room	Air	0.000	13:34
04	Std.	Gas	0.081	13:35
05	Room	Air	0.000	13:35
06	Std.	Gas	0.081	13:36
07	Room	Air	0.000	13:36

Sperator Signature NATHAN MORTEN

Remarks:

Form 106-18000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer<br/>North Dakota Model 8000Alcohol Analyzer<br/>SN 80-004956Location = COOP8164.14.00 09/1612/05/202313:38

	DRY CAL CHECK	
Test	AC	Time
01 Room Air 02 Room Air	RFI* RFI*	13:38 13:38
*Invalid Test		

Inhibited - RFI

Lot No = 14323080A1 Cyl No = 70 Exp Date = 06/05/2025 County = 20

Oper No. = 130095

Operator Signature

NATHAN MORTEN

Remarks:

Form 106-18000