

INTOXILYZER® 8000 INSTALLATION AND REPAIR CHECKOUT

NORTH DAKOTA OFFICE OF ATTORNEY GENERAL CRIME LABORATORY DIVISION-TOXICOLOGY SECTION/BREATH ALCOHOL PROGRAM SFN 59281 (06/2018)

Serial Number 80-003061	Instrument Location 6F56 - Jail			
Reason for Install/Repair				
☐ Install After Receiving From Crime Laboratory ☐ Install Aft	er Location Change			
Sother (Specify) Install after New	1 load/upland at UND PD			
Check When Done:				
1. Surge Protector Installed/Property Grounded.				
2. Telephone Line Connected to Intoxilyzer® 8000.				
7 3. Breath Tube Heated.				
4. Enter Preliminary Data (i.e. Date, Time, DST (Y), and Locat	ion; Level 2, Function E).			
5. Scan/Enter Gas Cylinder Information (Level 1, Function S).				
v 6. Run Tests:				
V A. Print Test (Level1, Function P).				
B_ACA Test (Level 1, Function C).				
C. Radio Frequency Interference (RFI) Test (CMS Mode or	Level 1, Function B or C; Key Radio During Test).			
7, Repair and/or Maintenance Performed (if any):				
8, Complete the Top Portion of the Intoxilyzer® Record (SFN5)	0496, Form 120-G) and Place it by the Intoxilyzer® for Use.			
9. File Previous Intoxilyzer® Record (SFN504096, Form 120-G) at the Intoxilyzer® Location at the Agency.				
10. Send the Following to the Crime Laboratory: Completed Into 104-G), Print Test, ACA Test, and RFI Test.	oxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form			
Field Inspector Signature	Date 03-07-24			
Crime Laboratory Use Only				
This installation has been reviewed and the instrument is approved to be	a used for the analysis of breath to determine alcohol concentration from			
the date the Field Inspector performed the installation. This record on fil County of Burleigh, North Dakota, is certified to be a true and correct co	e at the Office of Attorney General, Crime Laboratory Division, in the			
Reviewed/Certified By	Certified Date 07Mar2024			

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer Alcohol Analyzer
North Dakota Model 8000 SN 80-003061
Location = GFSO 8164.14.00 09/16
03/07/2024 14:20

******* Printer Test ********

abcdefghijklmnopqrstuvwxyz1234567890-=| ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&*()_+?

abcdefghijklmnopqrstuvwxyz1234567890-= |
ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&*() +?

Current Instrument Setup

Data Entry Mode: Enabled Start Test Sequence: DABACABA Display Prelim Rslt? Yes Display Third Digit? Yes Inhib Printer(Y/N)? No Display Volume? No Disable On Memfull? Yes # of Print Copies? Select Std (D/W/I)? Dry Standard Value? 0.080 Standard Lot #? 01923080A3 Standard Cyl #? 18 02/05/2025 Standard Expiration? Oper No? 133510

Flow Cal. Date: 03/04/2011 Slope 700 Intercept -623726

IR Calibration Date: 04/10/2015
3um 9um

Oth Coef(*100): -25722 -17879

1st Coef(*100): 266163 136703

2nd Coef(*100): 2302 1151

H2O adj(mg/l*10k): 412 294

******* Printer Test End ********

Operator Signature ADAM COLE

Remarks: Er in stell

Form 106-I8000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer North Dakota Model 8000 Location = GFSO 03/07/2024 Alcohol Analyzer SN 80-003061 8164.14.00 09/16 14:21

DRY CAL CHECK

Test	AC	Time
01 Room Air	0.000	14:22
02 Std. Gas	0.081	14:22
03 Room Air	0.000	14:23
04 Std. Gas	0.081	14:23
05 Room Air	0.000	14:23
06 Std. Gas	0.082	14:24
07 Room Air	0.000	14:24

Lot No = 01923080A3

Cyl No = 18

Exp Date = 02/05/2025

County = 18

Oper No. = 133510

Operator Signature ADAM COLE

Remarks:

for instal

Form 106-I8000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer
North Dakota Model 8000
Location = GFSO
03/07/2024

Alcohol Analyzer SN 80-003061 8164.14.00 09/16 14:25

Te	est	AC	Time
	Room Room	RFI* 0.000	14:27 14:27

*Invalid Test Inhibited - RFI

Sub Name = TEST, INSTALL NA

Sub DOB = 01/01/2000

Sub Sex = Male

Weight = 150

Cit = 1

Test = OTH
Dr. Lic. = ND/NA

Lot No = 01923080A3

Cyl No = 18

Expiration Date = 02/05/2025

County = 18

Oper No. = 133510

Operator Signature ADAM COLE

Remarks: for install

Form 106-I8000