

INTOXILYZER® 8000 INSTALLATION AND REPAIR CHECKOUT

NORTH DAKOTA OFFICE OF ATTORNEY GENERAL CRIME LABORATORY DIVISION-TOXICOLOGY SECTION/BREATH ALCOHOL PROGRAM SFN 59281 (06/2018)

Serial Number 80-003059 Instrument Location NEW YEAR, NI
Reason for Install/Repair
Install After Receiving From Crime Laboratory Install After Location Change
Other (Specify)
Check When Done:
1. Surge Protector Installed/Property Grounded.
2. Telephone Line Connected to Intoxilyzer® 8000.
3. Breath Tube Heated.
4. Enter Preliminary Data (i.e. Date, Time, DST (Y), and Location; Level 2, Function E).
5. Scan/Enter Gas Cylinder Information (Level 1, Function S).
6. Run Tests:
A. Print Test (Level1, Function P).
B. ACA Test (Level 1, Function C).
C. Radio Frequency Interference (RFI) Test (CMS Mode or Level 1, Function B or C; Key Radio During Test).
7. Repair and/or Maintenance Performed (if any): UPDSE
8. Complete the Top Portion of the Intoxilyzer® Record (SFN50496, Form 120-G) and Place it by the Intoxilyzer® for Use.
9. File Previous Intoxilyzer® Record (SFN504096, Form 120-G) at the Intoxilyzer® Location at the Agency.
10. Send the Following to the Crime Laboratory: Completed Intoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form 104-G), Print Test, ACA Test, and RFI Test.
Field Inspector Signature Down Mukan 22 AR 24
Crime Laboratory Use Only
This installation has been reviewed and the instrument is approved to be used for the analysis of breath to determine alcohol concentration from the date the Field Inspector performed the installation. This record on file at the Office of Attorney General, Crime Laboratory Division, in the County of Burleigh, North Dakota, is certified to be a true and correct copy of the documents received.

FORM 104-G

Reviewed/Certified By

Certified Date

29April2024

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer Alcohol Analyzer
North Dakota Model 8000 SN 80-003059
Location = NS 8164.14.00 09/16
04/22/2024 01:23

******** Printer Test ********

abcdefghijklmnopqrstuvwxyz1234567890-=|
ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&*()_+?

abcdefghijklmnopqrstuvwxyz1234567890-=|
ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&*()_+?

Current Instrument Setup

Enabled Data Entry Mode: Start Test Sequence: DABACABA Display Prelim Rslt? Yes Display Third Digit? Yes Inhib Printer(Y/N)? No No Display Volume? Disable On Memfull? Yes # of Print Copies? Select Std (D/W/I)? Dry Standard Value? 0.080 01923080A3 Standard Lot #? Standard Cyl #? 24 Standard Expiration? 02/05/2025 079706 Oper No?

Flow Cal. Date: 11/28/2018 Slope 589 Intercept -276335

IR Calibration Date: 12/04/2018
3um 9um

 0th Coef(*100):
 -25330
 -15825

 1st Coef(*100):
 278286
 137135

 2nd Coef(*100):
 1992
 1257

 H2O adj(mg/l*10k):
 525
 321

****** Printer Test End *******

Operator Signature DANA MIDDLETON

Remarks:

Form 106-I8000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer
North Dakota Model 8000
Location = NS
04/22/2024

SN 80-003059 8164.14.00 09/16 01:23

DRY CAL CHECK

	AC	Time
Air	0.000	01:24
Gas	0.081	01:25
Air	0.000	01:25
Gas	0.081	01:25
Air	0.000	01:26
Gas	0.081	01:26
Air	0.000	01:27
	Gas Air Gas Air Gas	Air 0.000 Gas 0.081 Air 0.000 Gas 0.081 Air 0.000 Gas 0.081

Lot No = 01923080A3

Cyl No = 24

Exp Date = 02/05/2025

County = 30

Oper No. = 079706

Operator Signature DANA MIDDLETON

Remarks:

Form 106-I8000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer
North Dakota Model 8000
Location = NS
04/22/2024

Alcohol Analyzer SN 80-003059 8164.14.00 09/16 01:28

Test	AC	Time
01 Room Air	RFI*	01:31
02 Room Air	RFI*	01:31

*Invalid Test Inhibited - RFI

Sub Name = RFI TEST, RFI RFI

Sub DOB = 10/10/1990

Sub Sex = Male

Weight = 150 Cit = NA

Test = OTH

Dr. Lic. = ND/NA Lot No = 01923080A3

Cyl No = 24

Expiration Date = 02/05/2025

County = 30

Oper No. = 079706

Operator Signature DANA MIDDLETON

Remarks:

Form 106-I8000