

## **INTOXILYZER® 8000 INSTALLATION AND REPAIR CHECKOUT** NORTH DAKOTA OFFICE OF ATTORNEY GENERAL CRIME LABORATORY DIVISION-TOXICOLOGY SECTION/BREATH ALCOHOL PROGRAM SFN 59281 (06/2018)

Install After Receiving From Crime Laboratory Install After Location Change					

- 1. Surge Protector Installed/Property Grounded.
- 2. Telephone Line Connected to Intoxilyzer® 8000.
- X 3. Breath Tube Heated.
- X 4. Enter Preliminary Data (i.e. Date, Time, DST (Y), and Location; Level 2, Function E).
- 5. Scan/Enter Gas Cylinder Information (Level 1, Function S).

X 6. Run Tests:

- X A. Print Test (Level1, Function P).
- B. ACA Test (Level 1, Function C).
- Z C. Radio Frequency Interference (RFI) Test (CMS Mode or Level 1, Function B or C; Key Radio During Test).
- 7. Repair and/or Maintenance Performed (if any):
- 🔀 8. Complete the Top Portion of the Intoxilyzer® Record (SFN50496, Form 120-G) and Place it by the Intoxilyzer® for Use.
- X 9. File Previous Intoxilyzer® Record (SFN504096, Form 120-G) at the Intoxilyzer® Location at the Agency.
- 10. Send the Following to the Crime Laboratory: Completed Intoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form X 104-G), Print Test, ACA Test, and RFI Test.

Field Inspector Signature

Crime Laboratory Use Only

This installation has been reviewed and the instrument is approved to be used for the analysis of breath to determine alcohol concentration from the date the Field Inspector performed the installation. This record on file at the Office of Attorney General, Crime Laboratory Division, in the County of Burleigh, North Dakota, is certified to be a true and correct copy of the documents received.

$\sim$		
Reviewed/Certified By	r hall	Certified Date 10May2024

Date

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501 CMI, Inc. Intoxilyzer Alcohol Analyzer North Dakota Model 8000 SN 80-006494 Location = CAVA 8164.14.00 09/16 21:55 04/05/2024 abcdefghijklmnopqrstuvwxyz1234567890-=| ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&\*()\_+? abcdefghijklmnopqrstuvwxyz1234567890-= ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&\*()\_+? Current Instrument Setup Data Entry Mode: Enabled Start Test Sequence: DABA Display Prelim Rslt? Yes Display Third Digit? Yes DABACABA No Inhib Printer(Y/N)? Display Volume? No Yes Disable On Memfull? # of Print Copies? 1 Dry 0.080 Select Std (D/W/I)? Standard Value? Standard Lot #? Standard Cyl #? 14323080A4 6 Standard Expiration? 06/05/2025 131669 Oper No? 08/18/2015 Flow Cal. Date: 655 Slope Intercept -624238 IR Calibration Date: 05/10/2017 3um 9um \_\_\_\_\_ -21478 Oth Coef(\*100): -28969 1st Coef(\*100):2565892nd Coef(\*100):2527 140860 1330 473 H2O adj(mg/l\*10k): 655 \*\*\*\*\*\*\*\*\* Printer Test End \*\*\*\*\*\*\*\*\*\*

Operator Signature LUKE OLSON

Remarks:

Form 106-I8000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. IntoxilyzerAlcohol AnalyzerNorth Dakota Model 8000SN 80-006494Location = CAVA8164.14.00 09/1604/05/202421:56

		[	DRY CAL CHECK	
Test			AC	Time
03 04 05 06	Room Std. Room Std. Room Std. Room	Gas Air Gas Air Gas	0.000 0.082 0.000 0.082 0.000 0.082 0.000 0.082	21:57 21:57 21:58 21:58 21:59 21:59 21:59 22:00

Lot No = 14323080A4 Cyl No = 6 Exp Date = 06/05/2025 County = 34

Oper No. = 131669

Operator Signature LUKE OLSON

Remarks:

Form 106-18000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501 Alcohol Analyzer CMI, Inc. Intoxilyzér North Dakota Model 8000 SN 80-006494 8164.14.00 09/16 Location = CAVA04/05/2024 22:01 Test AC Time 01 Room Air RFI\* 22:03 22:03 02 Room Air RFI\* \*Invalid Test Inhibited - RFI Sub Name = TEST, INSTALL INSTALL Sub DOB = 11/01/2000Sub Sex = Male Weight = 150Test = DUI Cit = 11111111111Dr. Lic. = ND/11111111111 Lot No = 14323080A4Cyl No = 6Expiration Date = 06/05/2025Oper No. = 131669County = 34

Operator Signature LUKE OLSON

Remarks:

RFI Check

Form 106-18000