

INTOXILYZER® 8000 INSTALLATION AND REPAIR CHECKOUT

NORTH DAKOTA OFFICE OF ATTORNEY GENERAL CRIME LABORATORY DIVISION-TOXICOLOGY SECTION/BREATH ALCOHOL PROGRAM SFN 59281 (06/2018)

Serial Number	Instrument Location	
80 - 60 59 4 ⁻ Reason for Install/Repair		Stat
	_	
Install After Receiving From Crime Laboratory	☐ Install After Location Change	
Other (Specify)		
Check When Done:		
Surge Protector Installed/Property Grounded		
2. Telephone Line Connected to Intoxilyzer® 80	000.	
3. Breath Tube Heated.		
4. Enter Preliminary Data (i.e. Date, Time, DST	(Y), and Location; Level 2, Function E)	
5. Scan/Enter Gas Cylinder Information (Level 1	1, Function S).	
6. Run Tests:		
A. Print Test (Level1, Function P).		
B. ACA Test (Level 1, Function C).		
C. Radio Frequency Interference (RFI) Test	(CMS Mode or Level 1, Function B or 0	C; Key Radio During Test).
7. Repair and/or Maintenance Performed (if any		
8. Complete the Top Portion of the Intoxilyzer®	Record (SFN50496, Form 120-G) and	Place it by the Intoxilyzer® for Use.
9. File Previous Intoxilyzer® Record (SFN50409	96, Form 120-G) at the Intoxilyzer® Loc	cation at the Agency.
10. Send the Following to the Crime Laboratory: 104-G), Print Test, ACA Test, and RFI Test.		
Field Inspector Signature		Date 5 28 24
Crime Laboratory Use Only		
This installation has been reviewed and the instrument is the date the Field Inspector performed the installation. To County of Burleigh, North Dakota, is certified to be a true	his record on file at the Office of Attorne	ev General Crime Laboratory Division in the
Reviewed/Certified By	Male	Certified Date 28May2024

FORM 104-G

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer Alcohol Analyzer
North Dakota Model 8000 SN 80-005944
Location = STAT 8164.14.00 09/16
05/28/2024 11:56

********* Printer Test ********

abcdefghijklmnopqrstuvwxyz1234567890-=|
ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&*()_+?

abcdefghijklmnopqrstuvwxyz1234567890-=|
ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&*()_+?

Current Instrument Setup
Data Entry Mode: Enabled

Start Test Sequence: DABACABA Display Prelim Rslt? Yes Display Third Digit? Yes Inhib Printer(Y/N)? No Display Volume? No Disable On Memfull? Yes # of Print Copies? 1 Select Std (D/W/I)? Dry Standard Value? 0.080 Standard Lot #? Standard Cyl #? 14323080A1 21

Standard Cyl #? 21 Standard Expiration? 06/05/2025 Oper No? 120906

Flow Cal. Date: 06/20/2013 Slope 677 Intercept -702620

IR Calibration Date: 04/30/2024
3um 9um

Oth Coef(*100): -17947 -24395
1st Coef(*100): 282873 138533
2nd Coef(*100): 2859 1378
H2O adj(mg/l*10k): 291 388

******* Printer Test End ********

Operator Signature PAMELA PEHL

Remarks:

Form 106-I8000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer
North Dakota Model 8000
Location = STAT
05/28/2024

Alcohol Analyzer SN 80-005944 8164.14.00 09/16 11:51

DRY CAL CHECK

Test			AC	Time
01	Room	Air	0.000	11:51
02	Std.	Gas	0.079	11:52
03	Room	Air	0.000	11:52
04	Std.	Gas	0.078	11:53
05	Room	Air	0.000	11:53
06	Std.	Gas	0.079	11:54
	Room		0.000	11:54

Lot No = 14323080A1

Cyl No = 21

Exp Date = 06/05/2025

County = 29

Oper No. = 120906

Operator Signature PAMELA PEHL

Remarks:

Form 106-I8000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer
North Dakota Model 8000
Location = STAT
05/28/2024

SN 80-005944 8164.14.00 09/16 11:58

DRY CAL CHECK

Test			AC	Time
01	Room	Air	RFI*	11:58
02	Room	Air	RFI*	11:58

*Invalid Test Inhibited - RFI

Lot No = 14323080A1

Cyl No = 21

Exp Date = 06/05/2025

County = 29

Oper No. = 120906

Operator Signature PAMELA PEHL

Remarks:

Form 106-I8000