

INTOXILYZER® 8000 INSTALLATION AND REPAIR CHECKOUT

NORTH DAKOTA OFFICE OF ATTORNEY GENERAL CRIME LABORATORY DIVISION-TOXICOLOGY SECTION/BREATH ALCOHOL PROGRAM SFN 59281 (06/2018)

Serial Number 80 -006493	Instrument Location Ward (ty Ja: 1		
Reason for Install/Repair			
☐ Install After Receiving From Crime Laboratory ☐ Install After	r Location Change		
Other (Specify) ONNUAL INSPECTION OF	Crime Laboratory		
	J		
Check When Done:			
1. Surge Protector Installed/Property Grounded.			
2. Telephone Line Connected to Intoxilyzer® 8000.			
図 3. Breath Tube Heated.		•	
4. Enter Preliminary Data (i.e. Date, Time, DST (Y), and Location	on; Level 2, Function E).		
5 Scan/Enter Gas Cylinder Information (Level 1, Function S).			
6. Run Tests:			
A Print Test (Level1, Function P).			
B. ACA Test (Level 1, Function C).			
C. Radio Frequency Interference (RFI) Test (CMS Mode or	Level 1, Function B or C; Key Radio Du	ring Test).	
7 Repair and/or Maintenance Performed (if any): // A			
8. Complete the Top Portion of the Intoxilyzer® Record (SFN50	0496, Form 120-G) and Place it by the Ir	ntoxilyzer® for Use.	
9. File Previous Intoxilyzer® Record (SFN504096, Form 120-G) at the Intoxilyzer® Location at the Agency.			
10. Send the Following to the Crime Laboratory: Completed Intoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form 104-G), Print Test, ACA Test, and RFI Test.			
Field Inspector Signature		Date	
282		06/27/2021	
Crime Laboratory Use Only			
This installation has been reviewed and the instrument is approved to be used for the analysis of breath to determine alcohol concentration from the date the Field Inspector performed the installation. This record on file at the Office of Attorney General, Crime Laboratory Division, in the County of Burleigh, North Dakota, is certified to be a true and correct copy of the documents received.			
Reviewed/Certified By	0	Certified Date 02Jul2024	

Current Instrument Setup Data Entry Mode: Enabled Start Test Sequence: DABACABA Display Prelim Rslt? Yes Display Third Digit? Yes Inhib Printer (Y/N)? No Display Volume? No Disable On Memfull? Yes # of Print Copies? 1 Select Std (D/W/I)? Dry Standard Value? 0.080 Standard Lot #? 14323080A4 Standard Cyl #? Standard Expiration? 06/05/2025 Oper No? 131334 Flow Cal. Date: 05/23/2018 Slope 640 Intercept -624033

IR (Calibration Da	te:	05/23/2018
		3um	9um
1st 2nd	Coef(*100): Coef(*100): Coef(*100): adj(mg/l*10k)	-19857 263752 3253 : 643	= 1000

******* Printer Test End *******

Operator Signature JOSHUA GUDVANGEN

Remarks:

Form 106-I8000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer
North Dakota Model 8000
Location = WARD
06/27/2024

Alcohol Analyzer SN 80-006493 8164.14.00 09/16 15:17

DRY CAL CHECK

Т	est		AC	Time
01	Room	Air	0.000	15:18
02	Std.	Gas	0.081	15:18
03	Room	Air	0.000	15:19
04	Std.	Gas	0.081	15:19
05	Room	Air	0.000	15:20
06	Std.	Gas	0.081	15:20
07	Room	Air	0.000	15:21

Lot No = 14323080A4

Cyl No = 44

Exp Date = 06/05/2025

County = 51

Oper No. = 131334

Operator Signature JOSHUA GUDVANGEN

Remarks:

Form 106-I8000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer	Alcohol Analyzer
North Dakota Model 8000	SN 80-006493
Location = WARD	8164.14.00 09/16
06/27/2024	15:22

Test	AC	Time
01 Room Air	0.000	15:25
02 Reference	RFI*	15:25
03 Room Air	0.000	15:25

*Invalid Test Inhibited - RFI

Operator Signature JOSHUA GUDVANGEN

Remarks:

Form 106-I8000