

INTOXILYZER® 8000 INSTALLATION AND REPAIR CHECKOUT

NORTH DAKOTA OFFICE OF ATTORNEY GENERAL CRIME LABORATORY DIVISION-TOXICOLOGY SECTION/BREATH ALCOHOL PROGRAM SFN 59281 (06/2018)

Serial Number 0 - 00 5 9 5 8	Instrument Location,	
Reason for Install/Repair		
Install After Receiving From Crime Laboratory Install After	er Location Change	
2 Other (Specify) Replacment		
Check When Done:		
1. Surge Protector Installed/Property Grounded.		
2. Telephone Line Connected to Intoxilyzer® 8000.		
3. Breath Tube Heated.		
4. Enter Preliminary Data (i.e. Date, Time, DST (Y), and Locat	ion; Level 2, Function E).	
5. Scan/Enter Gas Cylinder Information (Level 1, Function S).		
6. Run Tests:		
A. Print Test (Level1, Function P).		
B. ACA Test (Level 1, Function C).		
Radio Frequency Interference (RFI) Test (CMS Mode o	r Level 1, Function B or C; Key Radio Durin	g Test).
Z. Repair and/or Maintenance Performed (if any):	7	
8. Complete the Top Portion of the Intoxilyzer® Record (SFN5	0496, Form 120-G) and Place it by the Into	xilyzer® for Use.
9. File Previous Intoxilyzer® Record (SFN504096, Form 120-	G) at the Intoxilyzer® Location at the Agenc	y.
10. Send the Following to the Crime Laboratory: Completed In 104-G), Print Test, ACA Test, and RFI Test.	toxilyzer® 8000 Installation and Repair Che	ckout (SFN59281, Form
Field Inspector Signature	H534	ate 13/2024
Crime Laboratory Use Only		
This installation has been reviewed and the instrument is approved to the date the Field Inspector performed the installation. This record on County of Burleigh, North Dakota, is certified to be a true and correct of	file at the Office of Attorney General, Crime	ine alcohol concentration from Laboratory Division, in the
Reviewed/Certified/By	Narehood	certified Date

FORM 104-G

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer Alcohol Analyzer
North Dakota Model 8000 SN 80-005958
Location = DEVL 8164.14.00 09/16
12/13/2024 20:19

******* Printer Test ********

abcdefghijklmnopqrstuvwxyz1234567890-=|
ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&*()_+?

abcdefghijklmnopqrstuvwxyz1234567890-=|
ABCDEFGHIJKLMNOPQRSTUVWXYZ1@#\$%^&*() +?

Current Instrument Setup Data Entry Mode: Enabled Start Test Sequence: DABACABA Display Prelim Rslt? Yes Display Third Digit? Yes Inhib Printer(Y/N)? No Display Volume? No Disable On Memfull? Yes # of Print Copies? 1 Select Std (D/W/I)? Dry Standard Value? 0.080 Standard Lot #? Standard Cyl #? 14323080A4 Standard Expiration? 06/05/2025 132008 Oper No?

Flow Cal. Date: 06/21/2013 Slope 716 Intercept -760436

H20 adj(mq/l*10k): 425

IR Calibration Date: 04/07/2015

3um 9um

Oth Coef(*100): -17179 -17694

1st Coef(*100): 259328 130890

2nd Coef(*100): 3473 1654

****** Printer Test End ********

422

Operator Signature
WILLIAM EARL

Remarks:

Form 106-I8000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer
North Dakota Model 8000
Location = DEVL
12/13/2024

SN 80-005958 8164.14.00 09/16 20:27

DRY CAL CHECK

Test			AC	Time
01	Room	Air	0.000	20:28
02	Std.	Gas	0.081	20:28
03	Room	Air	0.000	20:29
04	Std.	Gas	0.081	20:29
05	Room	Air	0.000	20:30
06	Std.	Gas	0.081	20:30
07	Room	Air	0.000	20:31

Lot No = 14323080A4

Cyl No = 4

Exp Date = 06/05/2025

County = 36

Oper No. = 132008

Operator Signature WILLIAM EARL

Remarks:

Form 106-I8000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer Alcohol Analyzer
North Dakota Model 8000 SN 80-005958 Location = DEVL 12/13/2024

8164.14.00 09/16 20:24

DRY CAL CHECK

Test			AC	Time
01	Room	Air	0.000	20:25
02	Std.	Gas	0.081	20:25
03	Room	Air	0.000	20:26
04	Std.	Gas	RFI*	20:26
05	Room	Air	0.000	20:27

*Invalid Test Inhibited - RFI

Lot No = 14323080A4

Cyl No = 4

Exp Date = 06/05/2025

County = 36

Oper No. = 132008

Operator Signature WILLIAM EARL

Remarks:

Form 106-I8000