

INTOXILYZER® 8000 INSTALLATION AND REPAIR CHECKOUT

NORTH DAKOTA OFFICE OF ATTORNEY GENERAL CRIME LABORATORY DIVISION-TOXICOLOGY SECTION/BREATH ALCOHOL PROGRAM SFN 59281 (06/2018)

Serial Number 80-06687	Instrument Location			
Reason for Install/Repair				
Other (Specify)				
Check When Done:				
1. Surge Protector Installed/Property Grounded.				
3. Breath Tube Heated.				
4. Enter Preliminary Data (I.e. Date, Time, DST (Y), and Lo	cation; Level 2, Function E).			
☑ 5. Scan/Enter Gas Cylinder Information (Level 1, Function	S).			
☑ 6. Run Tests:				
A. Print Test (Level1, Function P).				
B. ACA Test (Level 1, Function C).				
C. Radio Frequency Interference (RFI) Test (CMS Mode	or Level 1, Function B or C; Key Radio During Test).			
Repair and/or Maintenance Performed (if any):				
Complete the Top Portion of the Intoxilyzer® Record (SF	N50496, Form 120-G) and Place it by the intoxilyzer® for Use.			
9. File Previous Intoxilyzer® Record (SFN504096, Form 120-G) at the Intoxilyzer® Location at the Agency.				
10. Send the Following to the Crime Laboratory: Completed 104-G), Print Test, ACA Test, and RFI Test.	Intoxilyzer® 8000 Installation and Repair Checkout (SFN59281, Form			
Field Inspector Signature	Date 4-29-25			
Crime Laboratory Use Only				
This installation has been reviewed and the instrument is approved the date the Field Inspector performed the installation. This record county of Burleigh, North Dakota, is certified to be a true and correct	to be used for the analysis of breath to determine alcohol concentration from on file at the Office of Attorney General, Crime Laboratory Division, In the st copy of the documents received.			
Reviewed/Certified By Anna Narehood	Certified Date 30April2025			

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer Alcohol Analyzer
North Dakota Model 8000 SN 80-006682
Location = CROS 8164.14.00 09/16
04/29/2025 22:34

******** Printer Test ********

abcdefghijklmnopqrstuvwxyz1234567890-=|
ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&*() +?

abcdefghijklmnopqrstuvwxyz1234567890-=|
ABCDEFGHIJKLMNOPQRSTUVWXYZ!@#\$%^&*()_+?

Current Instrument Setup

Enabled Data Entry Mode: Start Test Sequence: DABACABA Display Prelim Rslt? Yes Display Third Digit? Yes Inhib Printer(Y/N)? No Display Volume? No Disable On Memfull? Yes # of Print Copies? 1 Select Std (D/W/I)? Dry Standard Value? 0.080 Standard Lot #? 232492 Standard Cyl #? Standard Expiration? 10/05/2026 Oper No? 134037

Flow Cal. Date: 09/06/2016 Slope 701 Intercept -706193

IR Calibration Date: 09/06/2016 3um 9um

Coef(*100):	-17150	-23247
Coef(*100):	271726	134617
	831	1215
adj(mg/l*10k):	393	518
	Coef(*100): Coef(*100): Coef(*100): adj(mg/l*10k):	Coef(*100): 271726

****** Printer Test End ********

Operator Signature JAMES STACEY

Remarks:

Printer Test.

Form 106-I8000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer
North Dakota Model 8000
Location = CROS
04/29/2025

Alcohol Analyzer SN 80-006682 8164.14.00 09/16 22:42

DRY CAL CHECK

Test	AC	Time
01 Room Air	0.000	22:42
02 Std. Gas	0.082	22:43
03 Room Air	0.000	22:43
04 Std. Gas	0.081	22:44
05 Room Air	0.000	22:44
06 Std. Gas	0.081	22:45
07 Room Air	0.000	22:45

Lot No = 232492

Cyl No = 1

Exp Date = 10/05/2026

County = 12

Oper No. = 134037

Operator Signature
JAMES STACEY

Remarks:

Form 106-I8000

Intoxilyzer Test Record and Checklist NDOAG Crime Lab. Div., Bismarck, ND 58501

CMI, Inc. Intoxilyzer Alcohol Analyzer
North Dakota Model 8000 SN 80-006682
Location = CROS 8164.14.00 09/16
04/29/2025 22:46

Test	AC	Time
01 Room Air	0.000	22:48
02 *Subject Test	RFI*	22:49
03 Room Air	0.000	22:49

*Invalid Test Inhibited - RFI

Sub Name = DUMMY, DUMMY L

Sub DOB = 09/09/2000

Sub Sex = Male Weight = 230 Test = OTH Cit = 1

Dr. Lic. = ND/NA Lot No = 232492

Cyl No = 1

Expiration Date = 10/05/2026

County = 12 Oper No. = 134037

Operator Signature
JAMES STACEY

#4245

Remarks:

Form 106-I8000